# **ClickShare C-10**

Making hybrid collaboration flow in medium-sized and large meeting rooms



- Full BYOD support
- Seamless content sharing
- Full interactivity with touch back, blackboarding, annotation
- Enhanced security
- Connected and cloud managed
- Collaborate with the ClickShare Button or DesktopApp
- Delivered with 1 Button

Even in a hybrid meeting, participants can be engaged, inspired and active. ClickShare C-10 adds interactive features to full BYOD, easy wirless presentation in any medium to large meeting room. It is the wireless presentation hub that makes your hybrid meetings flow in one click.

## Find out what's new in the latest ClickShare update

## Full BYOD content sharing

With ClickShare C-10, you can start a meeting and get your content on screen within seconds. No matter the device you are using. Plug & Play with the ClickShare Button, that works perfectly on both Pc or Mac. Go for workflow integration with the ClickShare App on laptop, mobile or tablet. Or enable full BYOD on a 4K canvas: screen mirroring with Airplay, GoogleCast and Miracast works flawlessly.

Anyone, including guests, can share content wirelessly to the central room display with our one-click meeting experience. Two users can share side by side in full HD on screen. No cables, no software to download, no training needed.

## Enjoy interactive, creative meetings

ClickShare C-10 users can benefit from advanced interactive features including local view of the room display, decide what you share (either a full screen or a single window), annotation, blackboarding and touch back support that allows users to control the touchscreen in the room. Designed especially to make your meetings richer and more dynamic. C-10 makes hybrid collaboration flow in your creative meetings, brainstorms and discussion in one click.





### Enhanced security and seamless integration

Designed for enterprise rollouts, the IT-grade C-10 offers you enhanced security features (ISO27001 certified) and a wide range of connectivity options. With the XMS Cloud Management Platform you enjoy remote management of units and clear analytics to drive your digital workplace. For practical questions on network deployment of the ClickShare Conference range, check our technical support or get in touch with your Barco contact.

#### Boost collaboration in your existing fixed conference room

The ClickShare C-10 can be used stand-alone or in combination with your existing conference room. It empowers hybrid meetings in existing Microsoft Teams, Zoom or Webex conference rooms with simple, one-click wireless content sharing. ClickShare completes the existing set-up and makes hybrid collaboration flow. Designed to fit your business perfectly and evolve with it. With flexibility for the future built in, it's one of the smartest investments you can make in your meeting room or conference room ecosystem.

Custom SKU's apply in the APAC region. Please contact your supplier to know more.

Ceneral specifications       Operating system     Windows 8/81/10, mac OS 1013 and higher. Android v9 and higher (ClicKhare App)* 105.12 and higher (ClicKhare App)* 105.12 and higher (ClicKhare App)* 105.12 and higher (ClicKhare App)*       Video outputs     4K UH D (3840/2160) (e 301E 1DM11-4b)       Audio output     HDM       USB     1 X USB-A.1 X USB-C       ClicKhare Buttons     1       ClicKhare App     Decktop E Mobile       Native protocols     Amboj, Google Cast, Macast*       Native protocol     Max. 25dBA, g 0.30°C Max. 30dBA, g 0.40°C       Authonication protocol     WFA2 PSK on EEE 8021X using the ClicKhare Button In network integration mode WFA2 PSK on EEE 8021A spf / Macast       Wireless transmission protocol     IEEE 80211 Apf / Aca and IEEE 80215.1       Reach     ClicKhare Base Unit ClicKhare Base Uni	PRODUCT SPECIFICATIONS	CLICKSHARE C-10
Anoroid Va and higher (CickShare App)*   Video outputs 4K UHD (Sed0*2100) (g 30Hz HDM 14b   Audio output HDMI   USB 1X USB-A. 1X USB-C.   ClickShare Buttons 1   ClickShare App Desixtop 8 Mobile   Native protocols Airliay. Google Cast, Mincast*   Noise Level Max. S0BA (g 0-50°C Max. S0°C (g 0-50°C Max. S0°C (g 0-50°C Max. S0°C (g 0-50°C Marce 100°C Marce 10°C Marce Max. S0°C (g 0-50°C Marce 10°C Marce 10°C Max. S0°C (g 0-50°C Marce 10°C Marce 10°C Marce 10°C Max. S0°C (g 0-10°C Marce 10°C Marce 10°C Marce 10°C	General specifications	
Audio output     HDMI       USB     1 X USB-A, 1 X USB-C       ClickShare Buttons     1       ClickShare App     Desktop B Mobile       Native protocols     Airplay, Google Cast, Miracast*       Noise Level     Max 25dBA & 0-50°C       Max 25dBA & 0-50°C     Max 25dBA & 0-50°C       Max 25d BAB & 0-50°C     Max 25dBA & 0-50°C       Adutentiction protocol     IEEE B02.11 algn/ac and IEEE B02.15 uitsing the ClickShare Button in network integration mode       Wireless transmission protocol     IEEE B02.11 algn/ac and IEEE B02.15 uitsing the ClickShare Button in select number of countries)       Connections     1x USB Type-C 2.0 (ront): 1x USB Type A 2.0 (ront)       Temperature range     Operating: 0°C to +40°C (+43°F to +104°F)       Max: 35°C (BSF) at 300°C	Operating system	Android v9 and higher (ClickShare App)*
USB     1 X USB-A.1 X USB-C       ClickShare Buttons     1       ClickShare Buttons     1       ClickShare App     Desktop & Mobile       Noise Level     Max 250BA @ 0-30°C       Max 350BA @ 30.40°C     Max 350BA @ 30.40°C       Authentication protocol     WPA2-PSK is isand alone mode WPA2-PSK is used alone mode       WFRetest transmission protocol     UEEE 80211 alg/in/dac and IEEE 80215.1       Reach     Adjustable with signal strength modulation; max. 30m (100 ft) between ClickShare Button and ClickShare Base Unit Frequency band     2.4 CH2 and 5 CH2 (DPS chanels supported in select number of countries)       Connections     1 x Ethernet LAN 160t to US SST (PSF) as 3000m Storage 0 to 90% relative humidity, non-condensing Operation 0 to 90% relative humidity, non-condensing       Room Dock (peripheral support)     No       Local view of moderation*     Local view of moderation*       Network conn	Video outputs	4K UHD (3840*2160) @ 30Hz. HDMI 1.4b
ClickShare Buttons     1       ClickShare App     Desistop & Mobile       Native protocols     Airplay, Google Cast, Miacast*       Noise Level     Max. SoBA.e. 0.50°C Max. SoBA.e. 0.50°C Max. SoBA.e. 0.50°C       Authentication protocol     WPA2-PSK in stand alone mode WPA2-PSK or IEEE 802.11 wign the ClickShare Button in network integration mode       Wireless transmission protocol     IEEE 802.11 wign dive ClickShare Button in network integration mode       Wireless transmission protocol     IEEE 802.11 wign diversify modulation; max. 30m (100 R) between ClickShare Button and ClickShare Base Unit Prequency band 2.4 GHZ and 5 GHz       Frequency band     2.4 GHZ and 5 GHz (DFS channels supported in select number of countries)       Connections     1 % Ethernet LAN 1Gbit 1x USB Type-C 20 (mont). 1x USB Type A 2.0 (front)       Temperature range     Operation protocol     Storage: 0 to 90% relative humidity, non-condensing Operation: 0 to 85% relative humidity, non-condensing       Anti-thet system     Kensington lock     Certifications*     Kensington lock       Call view of moderation*     Local view of moderation*     Local view of moderation*       No     Certifications*     Certification*     Storage: 0 storage: 90 storage view storenetup view storage view storage view storenetup view s	Audio output	HDMI
ClickShare App     Desktop & Mobile       Noise Level     Max, 25dBA, a, 0-30°C (Max, 30dBA, a, 30-40°C)       Authentication protocol     WPA2-PSK in stand alone mode WPA2-PSK or IEEE 802.11 a/gIr/Asc and IEEE 802.15.1       Reach     Adjustable with signal strength modulation, max, 30m (100 ft) between ClickShare Button in network integration mode UKI is stand alone mode WPA2-PSK or IEEE 802.11 a/gIr/Asc and IEEE 802.15.1       Reach     Adjustable with signal strength modulation, max, 30m (100 ft) between ClickShare Button and ClickShare Baue Unit Frequency band 2.4 GHZ and 5 GHz [DFs channels supported in select number of countries)       Connections     1x Ethernet LAN (16bit Is UB Type 2.2 (front)! Ix USB Type A.2.0 (front)!       Temperature range     Operating: 0°C to +40°C (+42°F to +104°F) Max 38°C (95°F) at 3000m Storage: -20°C to +60°C (-4°F to +140°F)       Humidity     Storage: 0 to 90% relative humidity, non-condensing Operation: 0 to 85% relative humidity, non-condensing       Anti-theft system     Kensingtion lock       Certifications     FCC/CE       Touch screen support B Interactivity     Yes       Room Dock (peripheral support)     No       Local view # moderation*     Local view and moderation*       Network connection     Local view and moderation*       Network connection     Local view and moderation*       Neanagement and reportin	USB	1 X USB-A, 1 X USB-C
Native protocols     Airplay, Google Cast, Miracast*       Noise Level     Max. 25dBA (p. 0-30°C (Max. 30dBA (p. 0-30°C (Max. 30dBA (p. 0-30°C))       Authentication protocol     WPA2-P5K in stand alove mode WPA2-P5K on IEEE 802.11 <i>a/gh/ac</i> and IEEE 802.15.1       Reach     Adjustable with signal strength modulation, max. 30m (100 ft) between ClickShare Button and ClickShare Base Unit Frequency band       Connections     1/2 EE 802.11 <i>a/gh/ac</i> and IEEE 802.15 1       Reach     Adjustable with signal strength modulation, max. 30m (100 ft) between ClickShare Button and ClickShare Base Unit Frequency band       Connections     1/2 EHernet LAN 1Gbit 1/2 EHernet LAN 1Gbit 1/2 UBE Type A 2.0 (front)       Temperature range     Operating: OFC to +40°C [+32°F to +104°F] Max. 35°C (95°F) at 3000m Sicrage - 20°C to +40°C (-47°F to +140°F)       Humidity     Storage - 010 90% relative humidity, non-condensing Operation: 0 to 85% relative humidity, non-condensing       Anti-theft system     Kensington lock       Certifications     FCC/CE       Touch screen support 8 Interactivity     Yes       Room Dock (peripheral support)     No       Local view 4 moderation*     Local view and moderation*       Network connection     LN 9 WFI       Management and reporting     Yes       Warranty     1 year standard. 5 years	ClickShare Buttons	1
Noise Level     Max. 25dBA (b. 0-30°C Max. 30dBA (c) 30-0°C       Authentication protocol     WPA2-PSK in stand alone mode WPA2-PSK is stand in the stand is the stand is the stand is the stand is the stand ClickShare Button in network integration mode       Wireless transmission protocol     IEEE 802.11 al/g/n/ac and IEEE 802.15.1       Reach     Adjustable with signal strength modulation; max. 30m (100 ft) between ClickShare Button and ClickShare Base Unit Frequency band 24 GHZ and 5 GHz       Frequency band     2.4 GHZ and 5 GHz (DSZ channels supported in select number of countries)       Connections     Jx Ethernet LAN IColt Ix USB Type C.2.0 (front) Ix USB Type A 2.0 (front)       Temperature range     Operating O*C to +40°C [+32°F to +104°F) Max. 35°C (95°F) at 3000m Storage - 20°C to +60°C (-47°F to +140°F)       Humidity     Storage - 20°C to +60°C (-47°F to +140°F)       Humidity     Storage - 20°C to +60°C (-47°F to +140°F)       Humidity     Storage - 20°C to +60°C (-47°F to +140°F)       Atti-theft system     Kensington lock       Certifications     FCC/CE       Touch screen support Ø Interactivity     Yes       Room Dock (peripheral support)     No       Loca	ClickShare App	Desktop & Mobile
Max. 30dBA & 30-40°C       Authentication protocol     WPA2-PSK in stand alone mode WPA2-PSK in stand alone mode WPA2-PSK in stand alone mode WPA2-PSK in stand alone mode WPA2-PSK or IEEE 802.11 sugh/ac and IEEE 802.15.1       Reach     Adjustable with signal strength modulation; max. 30m (100 ft) between ClickShare Button and ClickShare Base Unit Frequency band     Z4 GH2 and 5 GH2       Frequency band     Z4 GH2 and 5 GH2 (DFS channels supported in select number of countries)       Connections     Ix Ethernet LAN 1Gbit Ix USB Type / 2.0 (front) Ix USB Type A 2.0 (front)       Temperature range     Operating '0C to +40°C (+32°F to +140°F)       Max: 35°C (95°P) at 3000m Storage - 20°C to +00°C (-44°F to +140°F)       Humidity     Storage 10 to 90% relative humidity, non-condensing Operation to to 85% relative humidity, non-condensing       Acti-theft system     Kensington lock       Certifications     FCC/CE       Touch screen support & Interactivity     Yes       No     Local view and moderation*       No WiFi       Management and reporting     Yes       Warnaty     1/9 ar standard.5 years coverage via SmartCare       •     * depends on configuration, available in future firmware updates       CitickShare Base Unit dimensions     Yes Name       Demosions (HxWxD)     34 mm x 135 mm </th <td>Native protocols</td> <td>Airplay, Google Cast, Miracast*</td>	Native protocols	Airplay, Google Cast, Miracast*
WPA2-PSK or IEEE 802.1X using the ClickShare Button in network integration mode       Wireless transmission protocol     IEEE 802.11 a/g/n/ac and IEEE 802.15.1       Reach     Adjustable with signal strength modulation; max. 30m (100 ft) between ClickShare Button and ClickShare Base Unit. Frequency band 2.4 GHZ and 5 GHz       Frequency band     2.4 GHZ and 5 GHz (DFS channels supported in select number of countries)       Connections     Ix Ethernet LAN IGbit USB Type-C.2.0 (front); 1x USB Type A.2.0 (front)       Temperature range     Operating 0°L to +40°C (+32°F to +104°F) Max. 55°C (95°F) at 3000m Storage -20°C to +60°C (+47°F to +140°F)       Humidity     Corage 0.16 poly: relative humidity, non-condensing Operation. 0 to 85% relative humidity.       Cound Screen support 6 Interactivity     Yes       Readement and reporting     Ves       Maranty     Yes       Waranty     Yes       Waranty     Yes       Dimensions (HxWxD)     Af mm x135 mm X135 mm       Power supply     Storage 10:0220 V AC plug       Power supply     Storage 10:0220 V AC plug	Noise Level	
Reach     Adjustable with signal strength modulation, max. 30m (100 ft) between ClickShare Button and ClickShare Base Unit Frequency band     Z4 GHZ and 5 GHZ       Frequency band     2.4 GHZ and 5 GHZ (DFS channels supported in select number of countries)       Connections     Jx Ethernet LAN 1Gbit Jx USB Type-C 2.0 (front); 1x USB Type A 2.0 (front)       Temperature range     Operating: 0°C to +40°C (+32°F to +104°F) Max: 35°C (95°F) at 3000m Storage: 20°C to +60°C (+4°F to +140°F)       Humidity     Storage: 0 to 90% relative humidity, non-condensing Operation: 0 to 85% relative humidity, non-condensing       Anti-theft system     Kensington lock       Certifications     FCC/CE       Touch screen support & Interactivity     Yes       Room Dock (peripheral support)     No       Local view & moderation     Local view and moderation*       Network connection     LN % WiFi       Maranty     1 year standard. 5 years coverage via SmartCare       *     * depends on configuration, avaitable in future firmware updates       ClickShare Base Unit dimensions     34 mm x 135 mm x 135 mm       Power supply     Standard 110/220 V AC plug       Power consumption     Operation2: 5-10W, 24W Max	Authentication protocol	
ClickShare Base Unit Frequency band 2.4 GHZ and 5 GHz     Frequency band   2.4 GHZ and 5 GHz     Frequency band   2.4 GHZ and 5 GHz     Connections   1x Ethernet LAN 1Gbit tx USB Type A 2.0 (front)     Temperature range   Operating: 0°C to +40°C (+32°F to +104°F) Max: 35°C (95°F) at 3000m storage: 20°C to A60°C (47°F to +140°F)     Humidity   Storage: 0 to 90% relative humidity, non-condensing Operation: 0 to 85% relative humidity, non-condensing     Anti-theft system   Kensington lock     Certifications   FCC/CE     Touch screen support 6 Interactivity   Yes     Room Dock (peripheral support)   No     Local view 4 moderation*   Local view and moderation*     Network connection   LAN 6 WiFi     Maranty   1 year standard. 5 years coverage via SmartCare     *   * depends on configuration, avaitable in future firmware updates     ClickShare Base Unit dimensions   34 mm x 135 mm     Power supply   Standard 10/220 V AC plug     Power supply   Standard 10/220 V AC plug	Wireless transmission protocol	IEEE 802.11 a/g/n/ac and IEEE 802.15.1
Connections1x Ethernet LAN 1Gbit 1x USB Type A 2.0 (front)Temperature rangeOperating: 0°C to +40°C (+32°F to +104°F) Max: 3°C (95°F) at 3000m Storage: -20°C to +60°C (-4°F to +140°F)HumidityStorage: -20°C to 0 90% relative humidity, non-condensing Operation: 0 to 85% relative humidity, non-condensing Operation: 0 to 85% relative humidity, non-condensing Core to 45°C (CETouch screen support 6 InteractivityYesRoom Dock (peripheral support)NoLocal view 6 moderationLocal view and moderation*Network connectionLAN 5 WiFiManagement and reportingYesWarranty1 year standard. 5 years coverage via SmartCare** depends on configuration, available in future firmware updatesClickShare Base Unit dimensions34 mm x 135 mm x 135 mmPower consumptionOperational: 5-10W, 24W Max	Reach	ClickShare Base Unit
1x USB Type-C 2.0 (front); 1x USB Type A 2.0 (front)     Temperature range   Operating: 0°C to +40°C (+32°F to +104°F) Max: 35°C (95°F) at 3000m Storage: -20°C to +60°C (-4°F to +140°F)     Humidity   Storage: 0 to 90% relative humidity, non-condensing Operation: 0 to 85% relative humidity, non-condensing     Anti-theft system   Kensington lock     Certifications   FCC/CE     Touch screen support & Interactivity   Yes     Room Dock (peripheral support)   No     Local view & moderation   Local view and moderation*     Network connection   LAN & WiFi     Maranty   1 year standard. 5 years coverage via SmartCare     *   * depends on configuration, available in future firmware updates     ClickShare Base Unit dimensions   34 mm x 135 mm     Power supply   Standard 110/220 V AC plug	Frequency band	2.4 GHZ and 5 GHz (DFS channels supported in select number of countries)
Max: 35°C (95°F) at 3000m Storage: -20°C to +60°C (-4°F to +140°F)     Humidity   Storage: 0 to 90% relative humidity, non-condensing Operation: 0 to 85% relative humidity, non-condensing     Anti-thef system   Kensington lock     Certifications   FCC/CE     Touch screen support 6 Interactivity   Yes     Room Dock (peripheral support)   No     Local view 6 moderation   Local view and moderation*     Network connection   LAN & WiFi     Maranty   1 year standard. 5 years coverage via SmartCare     *   * depends on configuration, available in future firmware updates     ClickShare Base Unit dimensions   34 mm x 135 mm     Power supply   Standard 110/220 V AC plug     Power consumption   Operational: 5-10W, 24W Max	Connections	
Operation: 0 to 85% relative humidity, non-condensing       Anti-theft system     Kensington lock       Certifications     FCC/CE       Touch screen support 6 Interactivity     Yes       Room Dock (peripheral support)     No       Local view 6 moderation     Local view and moderation*       Network connection     LAN 6 WiFi       Management and reporting     Yes       Varranty     1 year standard. 5 years coverage via SmartCare       *     depends on configuration, available in future firmware updates       ClickShare Base Unit dimensions     Standard 110/220 V AC plug       Power supply     Standard 110/220 V AC plug       Power consumption     Operational: 5-10W, 24W Max	Temperature range	Max: 35°C (95°F) at 3000m
Certifications   FCC/CE     Touch screen support & Interactivity   Yes     Room Dock (peripheral support)   No     Local view & moderation   Local view and moderation*     Network connection   LAN & WiFi     Management and reporting   Yes     Warranty   1 year standard. 5 years coverage via SmartCare     *   * depends on configuration, available in future firmware updates     ClickShare Base Unit dimensions   34 mm x 135 mm x 135 mm     Power supply   Standard 110/220 V AC plug     Power consumption   Operational: 5-10W, 24W Max	Humidity	
Touch screen support & Interactivity   Yes     Room Dock (peripheral support)   No     Local view & moderation   Local view and moderation*     Network connection   LAN & WiFi     Management and reporting   Yes     Warranty   1 year standard. 5 years coverage via SmartCare     *   * depends on configuration, available in future firmware updates     ClickShare Base Unit dimensions   34 mm x 135 mm x 135 mm     Power supply   Standard 110/220 V AC plug     Power consumption   Operational: 5-10W, 24W Max	Anti-theft system	Kensington lock
Room Dock (peripheral support)   No     Local view & moderation   Local view and moderation*     Network connection   LAN & WiFi     Management and reporting   Yes     Warranty   1 year standard. 5 years coverage via SmartCare     *   * depends on configuration, available in future firmware updates     ClickShare Base Unit dimensions   34 mm x 135 mm x 135 mm     Power supply   Standard 110/220 V AC plug     Power consumption   Operational: 5-10W, 24W Max	Certifications	FCC/CE
Local view & moderation Local view and moderation*   Network connection LAN & WiFi   Management and reporting Yes   Warranty 1 year standard. 5 years coverage via SmartCare   * * depends on configuration, available in future firmware updates   ClickShare Base Unit dimensions 34 mm x 135 mm x 135 mm   Power supply Standard 110/220 V AC plug   Power consumption Operational: 5-10W, 24W Max	Touch screen support & Interactivity	Yes
Network connectionLAN & WiFiManagement and reportingYesWarranty1 year standard. 5 years coverage via SmartCare** depends on configuration, available in future firmware updatesClickShare Base Unit dimensions34 mm x 135 mm x 135 mmDimensions (HxWxD)34 nm x 135 mm x 135 mmPower supplyStandard 110/220 V AC plugPower consumptionOperational: 5-10W, 24W Max	Room Dock (peripheral support)	No
Management and reportingYesWarranty1 year standard. 5 years coverage via SmartCare** depends on configuration, available in future firmware updatesClickShare Base Unit dimensions34 mm x 135 mm x 135 mmDimensions (HxWxD)34 ndard 110/220 V AC plugPower supplyStandard 110/220 V AC plugPower consumptionOperational: 5-10W, 24W Max	Local view & moderation	Local view and moderation*
Warranty   1 year standard. 5 years coverage via SmartCare     *   * depends on configuration, available in future firmware updates     ClickShare Base Unit dimensions   34 mm x 135 mm x 135 mm     Dimensions (HxWxD)   34 mm x 135 mm x 135 mm     Power supply   Standard 110/220 V AC plug     Power consumption   Operational: 5-10W, 24W Max	Network connection	LAN & WiFi
* * depends on configuration, available in future firmware updates   ClickShare Base Unit dimensions 34 mm x 135 mm x 135 mm   Dimensions (HxWxD) 34 mm x 135 mm x 135 mm   Power supply Standard 110/220 V AC plug   Power consumption Operational: 5-10W, 24W Max	Management and reporting	Yes
ClickShare Base Unit dimensions     Dimensions (HxWxD)   34 mm x 135 mm x 135 mm     Power supply   Standard 110/220 V AC plug     Power consumption   Operational: 5-10W, 24W Max	Warranty	1 year standard. 5 years coverage via SmartCare
Dimensions (HxWxD) 34 mm x 135 mm x 135 mm   Power supply Standard 110/220 V AC plug   Power consumption Operational: 5-10W, 24W Max	*	* depends on configuration, available in future firmware updates
Power supply Standard 110/220 V AC plug   Power consumption Operational: 5-10W, 24W Max	ClickShare Base Unit dimensions	
Power consumption Operational: 5-10W, 24W Max	Dimensions (HxWxD)	34 mm x 135 mm x 135 mm
	Power supply	Standard 110/220 V AC plug
Weight 900 gr	Power consumption	Operational: 5-10W, 24W Max
	Weight	900 gr

#### Last updated: 03 Jun 2021

Technical specifications are subject to change without prior notice. Please check www.barco.com for the latest information.

BARCO