

	Networked Audio				Ethernet	DSP	Channels			Watts Per Channel*				Low-Z / High-Z**	AUX Port	2x2 GPIO	Front Panel Display
	None	AVB	BLU link	Dante			2	4	8	300W	600W	1,250W	2,400W				
DCi 2 300	●						●			●				●	●		
DCi 2 600	●						●				●			●	●		
DCi 2 1250	●						●				●			●	●		
DCi 4 300	●							●		●				●	●		
DCi 4 600	●							●			●			●	●		
DCi 4 1250	●							●			●			●	●		
DCi 8 300	●								●	●				●	●		
DCi 8 600	●								●		●			●	●		
DCi 4 1250ND		●			●	●		●			●			●	●	●	●
DCi 8 600ND		●			●	●			●		●			●	●	●	●
DCi 2 300N			●		●	●	●			●				●	●	●	
DCi 2 600N			●		●	●	●				●			●	●	●	
DCi 2 1250N			●		●	●	●				●			●	●	●	
DCi 2 2400N			●		●	●	●					●		●	●	●	
DCi 4 300N			●		●	●		●		●				●	●	●	
DCi 4 600N			●		●	●		●			●			●	●	●	
DCi 4 1250N			●		●	●		●			●			●	●	●	
DCi 4 2400N			●		●	●		●				●		●	●	●	
DCi 8 300N			●		●	●			●	●				●	●	●	
DCi 8 600N			●		●	●			●		●			●	●	●	
DCi 4 300DA				●	●	●		●		●				●	●	●	
DCi 4 600DA				●	●	●		●			●			●	●	●	
DCi 4 1250DA				●	●	●		●			●			●	●	●	
DCi 8 300DA				●	●	●			●	●				●	●	●	
DCi 8 600DA				●	●	●			●		●			●	●	●	

\* Measured @ 4Ω; Continuous; All channels driven; 20Hz—20KHz; Minimum guaranteed power

\*\* Low-Z / High-Z configurable per individual channel; 70V / 100V configurable globally